

>> Blower Brushless AC

						
Series	TB 89 AC 145 mm	BB 89 AC 145 mm	BB 89 AC 182 mm	BB 89 AC 193 mm	BB 89 AC 226 mm	BB 158 AC 1Ph/ 3Ph 312 mm
Family	-	-	-	-	-	-
Type	Thru Flow	ByPass	ByPass	ByPass	ByPass	ByPass
Fan housing diameter (mm)	145	145	182	193	226	312
Fan stages	1 - 2	1 - 3	2	1	1	1
Max. airflow (m³/h)	221	455	195	400	930	2130
Max. pressure (kPa)	14.2	42.0	29.0	10.8	3.5	6.5
Rated voltage (VAC)	100-240 / 230	100-240 / 230	100-240 / 230	100-240 / 230	100-240 / 230	120 / 230 1ph 240 3ph
Max. power input (W)	600	1400	1800	1400	1400	4000
Speed control signal	On-Off / 0-10 V / PWM	On-Off / 0-10 V / PWM	On-Off / 0-10 V / PWM	On-Off / 0-10 V / PWM	On-Off / 0-10 V / PWM	On-Off / 0-10 V / PWM
Output signal	Tach Out / Failure Out	Tach Out / Failure Out	Tach Out / Failure Out	Tach Out / Failure Out	Tach Out / Failure Out	Tach Out / Failure Out

Universal voltage (100-240 VAC)						
Potentiometer for speed calibration						
Three phase AC input						
UL approval						

 Preferred series
 Standard product - MOQ may apply
 On request