

## Attendance, Incident and Satisfaction management



### TaqtOne FEATURES



Up to 5 capacitive buttons or up to 3 no-touch buttons.



Customizable front panel according to your need.



Antibacterial and antiviral film on the terminal.



Terminal designed and made in France.



Connectivity : LTE-M, NB-IoT and GSM. Works without a wifi connection.



A nominative or anonymous (NFC or magnet) tag.



Remote Firmware upgrade.



Autonomy : 2 to 8 years depending on usage with 6 AA batteries.



## CUSTOMIZABLE FRONT PANEL PER TYPE OF INTERVENTION :

### Improve your operational efficiency

Enhance operation traceability to achieve excellence.

### Improve team management

Alerts are sent to the staff in case of omission or absence.

### Inform and reassure

Users check on the screen the 6 latest interventions.



Import your team schedules in the platform.



Trace et track your daily operations easily.




Configure alerts based on your customer business rules.

## OPERATIONS MONITORING :

- Solved
- Solved but outside time range
- Planned
- Unsolved
- On-Demand request



Be notified in case of omission or staff absence, so that you can reschedule an intervention quickly !





## CUSTOMIZABLE FRONT PANEL PER TYPE OF INTERVENTION :

### Dissatisfaction detection

Users easily report any problem.

### On-Demand request

Notification is raised when a push button is triggered.

### Monitor incident remotely

All requests are available 24/7 on the platform.

## IMPROVE YOUR MONITORING AND INCIDENT RESPONSE :



Create team alert recipients by Email, SMS or through our ticketing module.




Add information like the location and type of incident.



Assign task to your team and monitor incident progress and resolution.



Anticipate issues and better respond to customer needs.



## CUSTOMIZABLE FRONT PANEL PER TYPE OF INTERVENTION :

### Measure satisfaction (CSAT)


Get customer satisfaction level and plan actions accordingly.

### Improve quality of service

The system identifies key moments for intervention and reinforced perceived quality.

### Build trust

Share the CSAT report with your client.



## MONITOR CONTINUOUSLY CUSTOMER SATISFACTION :




Define new call-to-action thresholds: number of consecutive red pushes, % of dissatisfaction...




Build and Analyze new SLAs (Response Time, MTTR, ...)



Share reports within your team and with your customer.



Empower your teams by showing the positive impact they have on user satisfaction.



MEET THE NEW NEEDS OF YOUR CUSTOMERS.

**Offer a contactless experience for more safety and comfort.**

*Position your finger 2 cm away from the button, a led blinks, the push is recorded.*

Model and Warranty	Model TAQT ONE - 1 year warranty (Extended warranty options).
Installation	Double-sided tape (included). Instructions included. Screw fixing (option).
Autonomy	1.5 year to 8 years autonomy depending on activated features and usage (6 AA LR6 lithium recommended).
Screen	Very low power E-ink technology screen. Display up to 6 lines.
Communication	LTE-M / NB-IOT / 2G connectivity.
Evolutive terminal	Customizable front panel according to your business case (or use case).
Capacitive buttons	0 to 5 customizable buttons. Activated remotely according to the chosen front panel.
Contactless buttons	Up to 3 customizable No Touch buttons - Put your finger at 2 cm away from the buttons to trigger a notification.
Firmware Upgrade (FoTA)	Firmware upgrade Over the Air (Update, configuration change).
Clock-in	Anonymous badging with magnet. Nominative badging with NFC tag.
Platform	Dashboards and data available on app.taqt.com (subscriptions).
Antimicrobial and antiviral surface	ANTIMICROBIAL FILM HEXIS PURE ZONE® PURZON060B - Bacterial reduction > 99.99% & Antiviral activity, on human coronavirus HCoV-229E strain (according to ISO 21702 standard) : -94.99 % after 15 min of contact -99.87 % after 60 min of contact.
Origin	Terminal designed & manufactured in France.
Weight and dimensions	Approx. 0.4 Kg. Minimum size 15.2 x 21.5 x 2.4 cm.
Waterproofing and mechanical resistance	IP6X waterproofing - (indoor usage only) - Tropicalisation and waterproofing options (not included). IK07 protection (usual shocks).
Certification	CE Certification.

