



TRANSFORMER®

Hose reel
optional

Patented solution



>1450

Rpm
Industrial

Idrobase Industrial
Pump VS Idrobase
Professional Pump



Video
Transformer



NEW INCLUDED

Pump maintenance
set 750hours



Maintenance
set page 540

Technical features

Code	Model	Version	Pressure	Flow rate	Rpm	Power	Weight
With Idrobase pump - Industrial							
ZX.2666-TS	1450 150/15 TS	Total Stop	150bar	15l/min	1450	5,5hp/4,0kW (3x400V-50Hz)	74kg
ZX.2667-TS	1450 150/21 TS	Total Stop	150bar	21l/min	1450	7,5hp/5,5kW (3x400V-50Hz)	88kg
ZX.2668-TS	1450 200/15 TS	Total Stop	200bar	15l/min	1450	7,5hp/5,5kW (3x400V-50Hz)	88kg
With Interpump pump							
ZX.2217-TS	1450 200/14 TS	Total Stop	200bar	14l/min	1450	7,5hp/5,5kW (3x400V-50Hz)	88kg

See also the corresponding hot water pressure washer: Stella page 518

Optional	Code	Description		ZX.2666-TS	ZX.2667-TS	ZX.2668-TS	ZX.2217-TS
	ZL.1V755Z	Lunga Double lance kit 1 with spray gun PRO1 M22x1,5 M, diverter with anodized aluminum body, professional foam lance ø2.1mm, with detergent injector ø1.4mm and filter with non-return valve		•	•	•	•
	ZL.1X8-B5G	Piuma Double lance equipped with diverter with anodized aluminum body and Piuma Aluminium foam lance			•		
	ZN.CC100B3P3P	H.p. hose R1 5/16", 315bar, 10m, M22x1,5 F-F		•	•	•	•
	ZN.CC150B3P3P	H.p. hose R1 5/16", 315bar, 15m, M22x1,5 F-F		•	•	•	•
	ZN.CC200B3P3P	H.p. hose R1 5/16", 315bar, 20m, M22x1,5 F-F		•	•	•	•
	ZX.2151	Hose reel kit composed of: painted support, manual hose reel and connection hose (WITHOUT H.P. HOSE)		•	•	•	•
	CDR.7062-L	Hose connection, M22x1,5 M-M		•	•	•	•
	ZY.040-T6M	Terminal with rotating nozzle - 040					•
	ZY.045-T6M	Terminal with rotating nozzle - 045				•	
	ZY.050-T6M	Terminal with rotating nozzle - 050		•			
	ZY.070-T6M	Terminal with rotating nozzle - 070			•		
	ZS.040-T6M	Terminal with sandblasting head - 040					•
	ZS.045-T6M	Terminal with sandblasting head - 045				•	
	ZS.050-T6M	Terminal with sandblasting head - 050		•			
	ZS.070-T6M	Terminal with sandblasting head - 070			•		
	ZX.2345	Tank holder bracket in stainless steel AISI 304 with 5L tank		•	•	•	•

Data, tables and pictures are purely indicative. Any changes can be made by the manufacturer without prior notice.

Technical features

- **Frame set** made of chromed steel and protected by transparent paint
- **Cover** made of thermoformed polystyrene
- **Industrial pump** 1450rpm, with crankshaft, brass head, 3 ceramic plungers

- **Electric motor** 1450Rpm 50Hz, complete with circuit breaker switch and 5m electric cable
- **Dimensions WxLxH:** 815 x 590 x 1042mm

Standard equipment

- **H.p. hose** 10m with screw quick couplings
- **Professional spray gun** w/extension
- **Lance extension** 580mm
- **H.p. nozzle** 25° high resolution