



# Technical features

Code	Model	Version	Pressure	Flow rate	Rpm	Temperature	Power	Weight
ZX.2153-TS	1450 200/15 TS	Total Stop	200bar	15I/min	1450	45 - 90°C *	7,5hp/5,5kW (3x400V-50Hz)	152kg

# Maintenance sets

ZX.75IBG08	Preventive maintenance 750 hours pump TS 200/15I
ZX.150IBG08	Preventive maintenance 1500 hrs pump TS 200/151
ZX.75ST-A	Preventive maintenance E - Stella HP washer 750 hours 200/151
ZX.300ST-B	Preventive maintenance F - Stella HP washer 3000 hours 200/15l



Optional	Code	Description	ZX.2152-TS	ZX.2153-TS	ZX.2154-TS	ZX.2214-TS
	ZL.1V755Z	Lunga Double lance kit 1 with spray gun PRO1 M22x1,5 M, diverter with anodized aluminium body, professional foam lance ø2.1mm, with detergent injector		•		٠
	ZL.1V7-H5Z	ø1.4mm and filter with non-return valve	•			
-	ZL.1X8-B5G	Piuma Double lance complete with diverter with anodized aluminium body and Piuma Aluminium foam lance			•	
0	ZN.CC100B3P3P	H.p. hose R1 5/16" 10m, M22x1,5 F-F	•	•	•	•
	ZN.CC150B3P3P	H.p. hose R1 5/16" 15m, M22x1,5 F-F	•	•	•	•
	ZN.CC200B3P3P	H.p. hose R1 5/16" 20m, M22x1,5 F-F	•	•	•	•
	CDR.7062-L	Hose connection, M22x1,5 M-M	٠	•	•	•
	ZX.1618-040	Set of h.p. quick nozzles - 040				•
	ZX.1618-045	Set of h.p. quick nozzles - 045		•		
	ZX.1618-050	Set of h.p. quick nozzles - 050	•			
	ZX.1618-070	Set of h.p. quick nozzles - 070			•	
	ZX.1271-900	CdR 80 lance, 900mm, with rotating nozzle flow rate 040				•
	ZX.1272-900	CdR 80 lance, 900mm, with rotating nozzle flow rate 045		•		
	ZX.1273-900	CdR 80 lance, 900mm, with rotating nozzle flow rate 050	•			
	ZX.1274-900	CdR 80 lance, 900mm, with rotating nozzle flow rate 070			•	
	ZX.1281-900	CdR 80 lance, 900mm, with sandblast nozzle flow rate 040				•
0	ZX.1282-900	CdR 80 lance, 900mm, with sandblast nozzle flow rate 045		•		
	ZX.1283-900	CdR 80 lance, 900mm, with sandblast nozzle flow rate 050	•			
	ZX.1285-900	CdR 80 lance, 900mm, with sandblast nozzle flow rate 075			•	
0	ZX.KAC10F	Hose for sewer nozzles 1/4" 210bar 10m, inlet M long, SS nozzle with 3 bottom holes, f.r. 045		•		•
	ZX.KAC10G	Hose for sewer nozzles 1/4" 210bar 10m, inlet M long, SS nozzle with 3 bottom holes, f.r. 055	•			
	ZX.KAC10V	Hose for sewer nozzles 1/4" 210bar 10m, inlet M long, SS nozzle with 3 bottom holes, f.r. 070			•	

Data, tables and pictures are purely indicative. Any changes can be made by the manufacturer without prior notice.

### Technical features

- **Tubular frame** set made of chromed steel treated with polyester
- Cover made of thermoformed polystyrene
- Industrial pump 1450rpm, with crankshaft, stainless steel head, 3 ceramic plungers
- Electric motor 1450rpm, 50Hz, complete with IP55 electric box with magneto-thermal ON/OFF switch and 5m power cable
- Heater with AISI 430 stainless external side coating, made of grey painted steel, galvanised steel inner jacket and stainless steel chimney
- Burner with delayed ignition
- Fuel tank 14L with level indicator
- In line fuel filter 30microns
- **Dimensions WxLxH:** 570 × 790 × 860mm

# Standard equipment

- H.p. hose 8m with screw quick couplings
- Professional spray gun with female swivel ball quick coupling
- Lance 900mm with male quick coupling
- **H.p. nozzle** 25° high resolution



# **IDROBASE INDUSTRIAL SERIES** (200/15) **PUMP MAINTENANCE**

IDROBASE: A CASE NICE AND A CA

**Set B - pump** maintenance 750 hours consisting of:



750hrs - h.p. industrial pumps maintenance







Valves + O-Rings kit

Seal packing

O-rings for fastening plungers



0,5L Mineral oil for h.p. pumps 10ml Threadlocker medium 25ml Technical grease

# **Set B** - **pump** maintenance 1500 hours consisting of:



1500hrs - h.p. industrial pumps maintenance













Valves + O-Rings kit

Complete seal packing kit

**Plungers** fastening kit

Ceramic plungers set

Plunger oil seals kit

0,5L Mineral oil for h.p. pumps 10ml Threadlocker medium 25ml Technical grease









#### Maintenance sets



Pump maintenance 750 hours



Pump maintenance 1500 hours



Machine maintenance 750 hours



Machine maintenance 3000 hours

MADE CE

# **STELLA HP WASHER** (ZX.2153-TS)

# **MACHINE MAINTENANCE**

**Set E - machine** maintenance 750 hours consisting of:









By-pass valve service kit

Service kit for spray gun

**Fuel filter** 

25ml Technical grease


# **Set F** - **machine** maintenance 3000 hours consisting of:















Fuel nozzle, safety valve and 1/4"M h.p. nozzle (1)

Circuit breaker switches (2)



Protection kit for circuit breaker switches

Fuel filter (3) Insulating disc for heaters (4)

Pressure switch SMALL G1/4" M, 25bar (5)

Pressure switch 45bar (6)

25ml Technical grease 10ml Threadlocker medium

SMALL G1/4" M,

#### **ENGLISH**

Copyrights© to this catalogue belong to IDROBASE GROUP® Srl. Reading, reference and dissemination in paper or electronic formats for personal use are permitted. Use for commercial purposes is not permitted, nor is any type of alteration except with the written consent of IDROBASE GROUP® Srl.

This catalogue cancels and supersedes the earlier version.

This catalogue provides general information on the products supplied by IDROBASE GROUP® Srl.

It is intended for retailers, system engineers, designers and more generally, all those who are already adequately familiar with said products, the materials from which they are made, their characteristics, efficiency and operation; it is therefore not intended for consumers who, in order to handle, install or perform any operation with the goods described here, must necessarily contact qualified and skilled personnel.

Also, with regard to skilled personnel, this catalogue should be considered a mere commercial tool, not containing the necessary technical specifications - which may be obtained free of charge from Idrobase, and as such, not suitable for use as a single go-to reference tool for the design, construction or installation of any kind of system.

The illustrations, technical characteristics, functions and other information given here about individual products, systems, installations and the like are based on the current state of the art: however, only the most immediately applicable information can be reproduced here, without any consideration for the global data necessary to design, implement and install any system, which must therefore be carefully assessed by designers, system engineers and installers.

Therefore, for specific indications on all products in the catalogue, please contact our main office, where competent staff are always on hand to answer any additional queries.

All the illustrations reproduced here may be slightly different from actual products and therefore, they should simply be intended as closely representing real items.

We reserve the right to introduce changes in all the products. For this reason, too, it is advisable to directly contact our main office. In case of doubts regarding interpretation, the original Italian text will prevail.

When a new reprint is published, the present edition will no longer be valid.





# Idrobase Group Srl

Via dell'Industria, N. 25 35010 Borgoricco (PD) Italia

www.idrobasegroup.com













Recognition of maximum commercial reliability



