

## OPTIC HAND DRYER

## BLINDER LINE STEEL



REF: **CS-500-X**  
**WHITE LACQUERED METAL** Finish




REF: **CS-500-S/X**  
**SATIN STEEL** Finish



REF: **CS-500-I/X**  
**BRIGHT STEEL** Finish

GENERAL DESCRIPTION	TECHNICAL ESPECIFICATIONS
<p>-Optic hand dryer Blinder model who presents rotating nozzle dryer, compact design and maxim power and airflow.</p> <p>-Suitable for toilets with high intense traffic such as <b>airports, large hotels, sport centers, large recreational areas and large official organizations, among others.</b></p> <p>-These hand dryer also features easy maintenance, low noise levels and a high level of user safety, with anti-vandalism features.</p> <p>- Different finishes: WHITE METAL LACQUERED and STEEL SATIN / BRIGHT.</p> <p>- Operates by activating a proximity sensor.</p> <p>- Approvals: CE and SGS.</p>	Material
	METAL / STEEL
	Power
	2.500 W
	Voltage
	220 V
	Frecuency
	50 Hz
	Degree of protection
	IPX1
	Sound level (2 meters)
	65 dB
	Air temperature (T <sup>a</sup> =21 °C)
	34 °C
	Airflow
	270 m <sup>3</sup> /h
	Velocity
	108 km/h
	Electrical isolation
	Class I
	System
	Sensor. Powered by proximity
	Drying time
	10-15 seconds

MEASUREMENTS	WEIGHT	VOLUME
<b>PRODUCT</b> 	NET WEIGHT: 5,611 kg (without packaging)	-
<b>BOX</b> (1 Unit)	GROSS WEIGHT: 6 kg (with packaging)	0,207 m <sup>3</sup>
<b>STANDARD BOX</b> (4 Units)	25,4 kg	0,92 m <sup>3</sup>
<b>PALLET</b>	-	1,536 m <sup>3</sup>

DETAILS	UNITS
PALLET	UNITS
	48
	BOXES PER LAYERS
	4
	PALLET LAYERS
	3

APPROVED BY: Technical department	DATE: 25/07/2017	F 03.08.03
-----------------------------------	------------------	------------

Losdi, S.L., reserves the right to make final modifications to change without prior notice

D Polígono Industrial Sur Santiago Payá C/ Filà Domingo Miques, 4 Apartado de Correos 350 03801, Alcoy (Alicante), SPAIN

T (+34) 966 540 710

F (+34) 966 540 688

W losdi.com