



HIGH PRESSURE CLEANERS

Distributed by:

EXECUTIVE G2 4350 psi · 21 l/pm







Petrol Driven

Hot Water

Daily Usage

FIELDS OF APPLICATION

Energy
Councils
Equipment Yards
Cleaning Contractors
Boat Yards and Ports
Agricultural Equipment
Trains Depots and Sheds



The Jetwave® Executive™ G2 heavy duty professional hot water v-twin petrol powered by HONDA™ pressure washer revolutionary in its design and innovation. Australian engineered and assembled using only the best quality Italian and global components; it offers world first compact multi configurable modular design & cover protection to maximise safety, functionality and efficiency.











HERO INNOVATIONS



Protection

Formed stainless steel cover to safeguard components and for work site safety.



Smart

Industry first customisable modular build with precision heavy gauge, steel chassis. Build it your way.



Functional

Easily accessible one panel facia mounted control(s).



Optimise

Anti-vibration protection system for quieter performance.



Convenient

Top lifting eyelets/tie down points and forklift tyne pockets for onsite lifting ability.



Featured

J5000™ Durotech™ Gun with swivel and ceramic ball.



Versatile

Multiple hose reel configurations.

STANDOUT FEATURES



JW professional Italian triplex plunger pump delivers performance and longer life.



Low Speed professional pump for increased reliability and longer maintenance intervals.



Easy start HONDA™GX630 Industrial Series Engine.



Dual M22 screw hose quick coupling system.



Vertical 90% fuel efficient environmentally friendly 12V diesel fired burner system.



Stainless steel pressure gauge.



Stainless Steel Emergency Stop with shroud.



Jetwave Safety System™ (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.



Washable water inlet and diesel filter to ensure clean trouble free supply.



Easy electric key start



Integrated accessory storage for gun and lance.



Professional line accessories.



Zero brass adjustable unloader valve.



Battery Isolater with maintenance free battery enclosed in protective box..

GeniSys™ 12V Advanced Burner Control:

- Delay cooling feature
- Welded relay protection - Interrupted ignition
- Epoxy moisture resistance
- High ambient temp rating
- Flame sensor / photo eye



Jetwave Group

72–74 Richmond Road
Keswick I Adelaide
South Australia I 5035 I AU

+61 8 8371 3599

sales@jetwave.com.au

jetwave.com.au

Compact - Modular frame design with top lift/forklift pockets

Quality - Industry proven 'Italian' pump.

Protection - Designed for durability and a long life.

Product Code

Flow Rate

TECHNICAL DATA

Working Pressure



Robust - Frame with gun and lance holder.

Control - Fascia - mounted controls with plug n' go functionality.

_ Power - Easy start V-TWIN HONDA™ GX630 engine.

Flexibility - Multi - configurable compact frame.

Shown with optional trolley kit & hose reel

psi / bar

l/pm

HW4350-21PEG2

4350 / 300

STANDARD EQUIPMENT

JW DUROTECH™ Gun - with M22 swivel and extension.



Lance / Nozzle - Dual lance with variable pressure control complete with hardened nozzles.



Hose - 15m of 3/8" double wire braided hose with quick coupling.

OPTIONAL ACCESSORIES

1. Complete Turbo Head with Lance	p/n	JWA160.05
2. Additional High Pressure Hose (per metre)	p/n	52001
3. High Pressure Swivel	p/n	Included
4. Foaming Lance with Bottle	p/n	JWA221-LS12
5. High Pressure Hose Reel Kit (cap 30m / 60m)	p/n	1060CMPL 1065CMPL
6. Hammerhead™ Whirlaway FSC 20" ABS	p/n	JWA-FSC21.05
7. Hammerhead™ Whirlaway FSC 22" Stainless Steel	p/n	JWA-FSC22.05
8. Giraffe™ Telescopic Lance	p/n	JWA-TELE7M.05
9. Sandblasting Kit	p/n	JWA164.05
10. Sludge Kit	p/n	80005.05

MACHINE OPTIONALS		
1. 316 Grade 2.5mm Stainless Steel Heating Coil	p/n	JWA322
2. Emergency Stop	p/n	Included
3. Battery Isolator	p/n	Included
4. Forklift Pockets	p/n	Included
5. Trolley Kit (including wheels, axles and soft grip handle)	p/n	JWA407 (4x offroad wheels) JWA408 (2x offroad wheels & 2x caster)
6. Stainless Steel Water Tank	p/n	90008-12





I tow Italic	Opini	21
Max Water Inlet / Outlet Temp	°c	60 / 90
INTENDED APPLICATION		
Usage Frequency	hours / type	4 - 8 daily / Daily
Category of Dirt / Debris	type	Heavy
Class (AS/NZS 4233:2013)	grade	В
,	3	
MOTOR FEATURES	tuno	HONDA™ CV620 (/, ctrake pir cooled)
Engine	type	HONDA™ GX630 (4 stroke, air cooled)
Power	СС	630
Fuel Supply	type	Unleaded
Fuel Capacity	litres	16
Low Oil Shutdown	y / n	Y (indicator light)
Hour Meter	y / n	Y (standard)
Starting System	type	Electric key start
HYDRAULIC FEATURES		
Pump / Head / Pistons	type	Italian Triplex Plunger / Brass / Ceramic
Motor Pump Coupling	type	Gearbox Drive
Pump Speed	rpm	1450
Unloader Valve	type	Independant (Zero)
Safety Valve	y / n	Υ
Orifice / Nozzle	size	055
OTHER FEATURES		
Electric / Key Start Available	y /n	Y (standard)
Adjustable Pressure	y / n	Υ
Hose Reel Provision	y / n	Y / 3 Positions
Frame Structure	type	Modular skid with heavy gauge steel and stainless steel cover
Onboard Accessory Storage	y / n	Υ
Detergent Injector	y / n	Y - Downstream low pressure adjustable
THERMAL FEATURES		
Burner Model	type	Vertical V Series
Fuel Supply	type	Diesel
Fuel Tank Capacity	litres	16
Burner Fuel Consumption (max)	l/ph	5.74
Coil	type	Mild steel 3mm wall seamless (400 bar rated)
Housing Material	type	Stainless Steel
DIMENSIONS & WEIGHT		
Approx Weight	kg	285 unit / 300 boxed
Unit Dimensions (skid)	mm	1090(L) x 680(W) x 900(H)
Boxed Dimensions	mm	1200(L) x 800(W) x 1400(H)
Number per Pallet	type: pieces	EUR0:1
WARRANTY(S)		
Engine Warranty	years	3 Engine Engine
Pump Warranty	years	2 2
Coil Warranty	years	2 2