

Distributed by:



## HIGH PRESSURE CLEANERS

# **HORNET © 2** 4060 psi ⋅ 15 l/pm







Petrol Driven

#### FIELDS OF APPLICATION

Roof Cleaning **Painting Contractors** Cleaning Contractors **Boat Yards and Ports** Agricultural Equipment Councils & Government







HONDA

The Jetwave® Hornet G2™ heavy duty professional cold water petrol powered by HONDA™ pressure washer is revolutionary in its design and innovation. Australian engineered and assembled using only the best quality Italian and global components; it offers an industry first multi configurable design to maximise space and efficiency.



#### **HERO INNOVATIONS**



#### Protection

Formed stainless steel cover to safeguard components and for work site safety.



### **Smart**

Industry first customisable modular build with precision heavy gauge, steel chassis. Build it your way.



#### **Functional**

Easily accessible singular panel mounted control(s).



Anti-vibration protection for a quieter reliable performance.



#### Convenient

Top lifting eyelets for onsite lifting ability.



#### **Featured**

J5000™ Durotech™ Gun with swivel and ceramic ball.



#### Versatile

Multiple hose reel configurations.

#### STANDOUT FEATURES



Professional JW Italian triplex plunger pump delivers performance and longer life.



Low speed professional pump for increased reliability and longer maintenance intervals.



Easy start HONDA™ GX390 Industrial Series OHV Engine.



Dual M22 screw hose coupling system.



Heavy duty washable inlet water filter.



Jetwave Safety System™ (JSS) thermal valve to prevent overheating in excessive bypass and over pressurisation.



Integrated accessory storage for gun and lance.



Professional line accessories.



Quality pressure gauge.



Zero line pressure brass adjustable unloader valve.



Optional key start.

Registered Design No.: 201710299



Jetwave Group 72-74 Richmond Road Keswick I Adelaide South Australia I 5035 I AU

+61 8 8371 3599

sales@jetwave.com.au

jetwave.com.au

#### STANDARD EQUIPMENT



Spray Gun -J5000™ heavy duty insulated back part lance and quick coupling.

#### Lance / Nozzle

- Stainless steel dual lance with variable pressure control complete with hardened nozzles.

Hose - 15m of 3/8" double wire braided hose with quick coupling.

#### **OPTIONAL ACCESSORIES**

	1. Complete Turbo Head with Lance	p/n	JWA160.04
	2. Additional High Pressure Hose (per metre)	p/n	52001
	3. High Pressure Swivel	p/n	26105000
	4. LS12 Foaming Lance with Tank	p/n	JWA221-LS12
	5. High Pressure Hose Reel (cap 30m or 60m)	p/n	1060CMPL 1067CMPL
	6. Hammerhead™ Whirlaway 21" ABS	p/n	JWA-FSC21.04
	7. Hammerhead™ Whirlaway 21" Stainless Steel	p/n	JWA-FSC22.04
	8. Engine Hour Meter	p/n	19598
	9. Giraffe™ Alloy Telescopic Lance	p/n	JWA-TELE7.3
	10. Sandblasting Kit	p/n	JWA164
	11. Sludge Kit	p/n	80005
	12. Drain Kit	p/n	H0P2X15VF
	MACHINE OPTIONALS		
	1. Stainless Steel Bypass Tank	p/n	90008-12G2
	2. Low level Water Cut Out	p/n	JWA220
	3. Flat Bed Mounting Kit	p/n	JWA406
	4. 5L Stainless Steel Chemical Holder	p/n	CHEM-5L

**JET**\V/A\/E HONDA

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement. V1.0 12/2019

Compact - Modular frame design with top lift panels.

Protection - Designed for durability and a long life.

Control - Fascia mounted controls with plug n' go functionality.



Robust - Frame with gun and lance holder.

Quality - Industry proven 'Italian' pump.

Power - Easy start HONDA™ GX390 engine.

Flexibility - Multi configurable compact frame.

Product Code	p/n	CW4000-15PG2
TECHNICAL DATA		
Working Pressure	psi / bar	4000 / 275
Flow Rate	l/pm	15
Max Water Inlet Temp	°c / °f	60 / 140
Class (AS/NZS: 4233)	grade	A
INTENDED APPLICATION		
Usage Frequency	hours / type	4 - 6 daily / Constant
Category of Dirt / Debris	type	Medium
MOTOR FEATURES		
Engine	type	HONDA™ GX390 (4 stroke, air cooled)
Power	hp / cc	13 / 390
Fuel Supply	type	Unleaded
Fuel Capacity	litres	6.1
Low Oil Shutdown	y / n	Υ
Hour Meter	y / n	N
Starting System	type	Recoil / Pull
HYDRAULIC FEATURES		
Pump / Head / Pistons	type	Interpump® Plunger Triplex / Brass / Ceramic
Motor Pump Coupling	type	Gearbox Drive
Pump Speed	rpm	1450
Unloader Valve	type	Independent (Zero)
Safety Valve	y / n	Υ
Orifice / Nozzle	size	040
OTHER FEATURES		
Electric / Key Start Available	y /n	Y (p/n: C4000-15PEG2)
Adjustable Pressure	y / n	Υ
Hose Reel Provision	y / n	Υ
Frame Structure	type	Modular skid with heavy gauge steel covers
Onboard Accessory Storage	y / n	Υ
Detergent Injector	y / n	Y - Downstream low pressure adjustable
DIMENSIONS & WEIGHT		
Approx Weight	kg	80 unit / 86 boxed
Unit Dimensions	mm	1110(L) x 700(W) x 860(H)
Boxed Dimensions	mm	970(L) x 600(W) x 670(H)
Number per Pallet	type: pieces	AS: 2 / Euro: 1
WARRANTY(S)		
Engine Warranty	years	3 Engine was likely
Warranty	years	1 1100

<sup>\*</sup>Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).