

XLERATOR® HAND DRYER



OPTIONAL HEPA FILTRATION

99.999%
REMOVAL OF VIRUSES
FROM THE AIRSTREAM*

50% LONGER LIFE. 7-YEAR WARRANTY.

NEW ENHANCED STANDARD FEATURES



Adjustable Speed and
Sound Control



Multi-Voltage Options:
110-120V Or 208-277V



Adjustable Heat Settings -
High, Medium, Low & Off



Externally Visible
Service LED

8
SECONDS¹
dry time

95%
COST SAVINGS
versus paper towels

3.7
WATT HOURS
energy use



XLERATOR® HAND DRYER



MODELS: **XL - BW** **W** **GR** **C** **SB** **SI** **SP** OPTIONS: **-1.1N** (Noise Reduction Nozzle) **-H** (HEPA Filter) **-VOLTAGE** (See Chart)



XL-BW

White Thermoset Resin (BMC)



DRY TIME: 8 SECONDS¹

ENERGY PER USE: 3.7 Wh



UL Environment published the first global Product Category Rules (PCR) for hand dryers which outlined industry consensus testing procedures to quantify environmental impact and performance. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in certified, internationally-recognized Environmental Product Declarations (EPDs). EPDs enable specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

FEATURES & BENEFITS

- ✓ 50% Longer Life
- ✓ Industry Leading 7-Year Limited Warranty
- ✓ 95% Cost Savings Vs. Paper Towels
- ✓ Helps Qualify For The Most LEED® Credits
- ✓ Made In USA Certified®
- ✓ A Hygienic Hand Drying Solution
- ✓ Washable Pre-Filter
- ✓ Adjustable Sensor Range

OPTIONS

- ✓ **HEPA Filtration System:** Removes 99.999% of viruses from the airstream.²
- ✓ **1.1" Noise Reduction Nozzle:** Reduces the sound level by 9 decibels by significantly decreasing air deflection noise while only increasing dry time by approximately 3 seconds.



XL-W

White Epoxy Painted



XL-GR

Graphite Textured Painted



XL-SP³

Custom Special Paint



XL-SI⁴

Custom Special Image



XL-C

Chrome Plated



XL-SB

Brushed Stainless Steel

PERFORMANCE

ADJUSTABLE SOUND LEVEL: 65-75 dB **ADJUSTABLE VELOCITY:** 13,000-20,000 LFM

ADJUSTABLE HEAT RANGE: 72°F-135°F **ADJUSTABLE FLOW RATE:** 42-63 CFM

DIMENSIONS

Width 11 3/4" (298 mm) **Height** 12 11/16" (322 mm) **Depth** 6 11/16" (170 mm)

ELECTRICAL

VOLTS	AMPS	WATTS	NO HEAT AMPS	NO HEAT WATTS	HERTZ	
110-120V	11.3-12.2A	1240-1450W	4.3-4.5A	460-530W	50/60 Hz	UL US
208-277V	5.6-6.2A	1160-1490W	2.0-2.2A	425-500W	50/60 Hz	UL US
230V	6.1A	1410W	2.2A	500W	50 Hz	CE

CERTIFICATIONS



WEIGHT

XL-BW: 15 lbs. (6.8 kgs.) **XL-SB:** 16 lbs. (7.26 kgs.) **XL-W, GR, C, SI, SP:** 17 lbs. (7.71 kgs.)

ACTIVATION

Automatic Sensor Operated

MOUNTING

Surface Mounted

SUGGESTED MOUNTING HEIGHTS

Men 45" (114 cm) **Women** 43" (109 cm) **Accessible** 37" (94 cm)

Note: Heights measured from floor to bottom of dryer.

ACCESSORIES

- ✓ Antimicrobial Wall Guards (#89B, #89W, #89S)
- ✓ XChanger® Paper Towel Dispenser Retrofit Kit (#40575, #40550)
- ✓ ADA-Compliant Recess Kit (#40502)

#40502



¹Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.

²Based on testing performed by LMS Technologies, April 2020. ³Special Paint powder-coated covers are available in many colors and textures. ⁴Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.



TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

**AUG
2020**

19XLS0776

XLERATOReco[®] HAND DRYER



OPTIONAL HEPA FILTRATION
99.999%
REMOVAL OF VIRUSES
FROM THE AIRSTREAM¹

50% LONGER LIFE. 7-YEAR WARRANTY.

NEW ENHANCED STANDARD FEATURES



Adjustable Speed and
Sound Control



Multi-Voltage Options:
110-120V Or 208-277V



500 Watts
No Heat



Externally Visible
Service LED

10
SECONDS¹
dry time

95%
COST SAVINGS
versus paper towels

1.7
WATT HOURS
energy use



XLERATOR^{eco}® HAND DRYER



MODELS: **XL - BW** **W** **GR** **C** **SB** **SI** **SP** - **ECO** OPTIONS: **-1.1N** (Noise Reduction Nozzle) **-H** (HEPA Filter) **-VOLTAGE** (See Chart)



XL-BW-ECO

White Thermoset Resin (BMC)



DRY TIME: 10 SECONDS'

ENERGY PER USE: 1.7 Wh



UL Environment published the first global Product Category Rules (PCR) for hand dryers which outlined industry consensus testing procedures to quantify environmental impact and performance. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in certified, internationally-recognized Environmental Product Declarations (EPDs). EPDs enable specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

FEATURES & BENEFITS

- ✓ 50% Longer Life
- ✓ Industry Leading 7-Year Limited Warranty
- ✓ 95% Cost Savings Vs. Paper Towels
- ✓ Helps Qualify For The Most LEED® Credits
- ✓ No Heat Technology
- ✓ Made In USA Certified®
- ✓ A Hygienic Hand Drying Solution
- ✓ Washable Pre-Filter

OPTIONS

- ✓ **HEPA Filtration System:** HEPA Filtration System Filters out 99.999% of viruses from the airstream²
- ✓ **1.1" Noise Reduction Nozzle:** Reduces the sound level by 9 decibels by significantly decreasing air deflection noise while only increasing dry time by approximately 3 seconds.



XL-W-ECO

White Epoxy Painted



XL-GR-ECO

Graphite Textured Painted



XL-SP-ECO³

Custom Special Paint



XL-SI-ECO⁴

Custom Special Image



XL-C-ECO

Chrome Plated



XL-SB-ECO

Brushed Stainless Steel

PERFORMANCE

ADJUSTABLE SOUND LEVEL: 65-75 dB **ADJUSTABLE VELOCITY:** 13,000-20,000 LFM

FLOW RATE: 43-65 CFM

DIMENSIONS

Width 11 3/4" (298 mm) **Height** 12 11/16" (322 mm) **Depth** 6 11/16" (170 mm)

ELECTRICAL

VOLTS	AMPS	WATTS	HERTZ	
110-120V	4.3-4.5A	460-530W	50/60 Hz	UL US
208-277V	2.2-2.2A	425-500W	50/60 Hz	UL US
230V	2.2A	500W	50 Hz	CE

NOTE: Drawing 4.5 Amps or less allows for the installation of multiple XLERATOReco units on one circuit, significantly reducing installation costs and creating a return on investment of less than one year.

CERTIFICATIONS



RoHS

WEIGHT

XL-BW-ECO: 15 lbs. (6.8 kgs.)

XL-SB-ECO: 16 lbs. (7.26 kgs.)

XL-W-ECO, XL-GR-ECO, XL-C-ECO, XL-SI-ECO, XL-SP-ECO: 17 lbs. (7.71 kgs.)

ACTIVATION

Automatic Sensor Operated

MOUNTING

Surface Mounted

SUGGESTED MOUNTING HEIGHTS

Men 45" (114 cm)

Women 43" (109 cm)

Accessible 37" (94 cm)

Note: Heights measured from floor to bottom of dryer.

ACCESSORIES

- ✓ Antimicrobial Wall Guards (#89B, #89W, #89S)
- ✓ XChanger® Paper Towel Dispenser Retrofit Kit (#40575, #40550)
- ✓ ADA-Compliant Recess Kit (#40502)

#40502



¹Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers. ²Based on testing performed by LMS Technologies, April 2020. ³Special Paint powder-coated covers are available in many colors and textures. ⁴Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.



TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

**AUG
2020**

19ECS0778

ThinAir® HAND DRYER



OPTIONAL HEPA FILTRATION
99.999%
REMOVAL OF VIRUSES
FROM THE AIRSTREAM

SURFACE MOUNTED. ADA COMPLIANT.

NEW ENHANCED STANDARD FEATURES



Adjustable Speed and
Sound Control



Multi-Voltage Options:
110-120V Or 208-277V



Adjustable Heat Settings -
High, Medium, Low & Off



Externally Visible
Service LED

14
SECONDS¹
dry time

95%
COST SAVINGS
versus paper towels

80%
LESS ENERGY
than conventional dryers



ThinAir® HAND DRYER



MODELS: **TA - ABS** **W** **GR** **SB** **SI** **SB-SI** **SP** **-H** (HEPA Filter) **-VOLTAGE** (See Chart)



TA-ABS

White Polymer (ABS)
With SanaFor™ Antimicrobial Additive



DRY TIME: 14 SECONDS¹

ENERGY PER USE: 3.7 Wh¹



UL Environment published the first global Product Category Rules (PCR) for hand dryers which outlined industry consensus testing procedures to quantify environmental impact and performance. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in certified, internationally-recognized Environmental Product Declarations (EPDs). EPDs enable specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

FEATURES & BENEFITS

- Meets 4" ADA protrusion guidelines when surface mounted
- 95% Cost Savings Vs. Paper Towels
- Made In USA Certified®
- 5-Year Limited Warranty
- BuildingGreen Approved and Helps Qualify for several LEED® credits
- A Hygienic Hand Drying Solution
- Washable Pre-Filter

OPTIONS

- HEPA Filtration System:** Removes 99.999% of viruses from the airstream²

OPTIONAL ACCESSORIES

- Antimicrobial Wall Guards:

• **89W** Microban® Wall Guard - White • **89B** Microban Wall Guard - Black • **89S** Wall Guard - Brushed Stainless Steel



TA-W
White Epoxy Painted



TA-GR
Graphite Textured Painted



TA-SP²
Custom Special Paint



TA-SI²
Custom Special Image



TA-SB
Brushed Stainless Steel



TA-SB-SI¹
Brushed Stainless Steel Special Image

OVERALL DIMENSIONS

Width: 9 5/32" (233 mm) **Height:** 13 15/16" (354 mm) **Depth:** 3 15/16" (100 mm)

WEIGHT

TA-ABS: 8 lbs. (3.6 kgs.)

TA-W, TA-GR, TA-SP, TA-SI, TA-SB, TA-SB-SI: 10 lbs. (4.5 kgs.)

PERFORMANCE

ADJUSTABLE SOUND LEVEL: 69 - 73 dB **ADJUSTABLE VELOCITY:** 12,000 - 17,000 LFM

ADJUSTABLE HEAT RANGE: 95°F - 136°F **FLOW RATE:** 29 - 42 CFM

ELECTRICAL

Units are Single Phase; 950 Watts or as low as 300 Watts (without heat) and available as specified in:

VOLTS	AMPS	WATTS	NO HEAT AMPS	NO HEAT WATTS	HERTZ	
110-120V	7-7.7A	770-915W	3-3.2A	310-370W	50/60 Hz	cUL US
208-277V	3.6-4A	735-950W	1.5-1.9A	300-375W	50/60 Hz	cUL US
230V	3.9A	890W	1.7A	375W	50 Hz	CE

CERTIFICATIONS



ACTIVATION

Automatic Sensor Activated

MOUNTING

Surface-Mounted

ADA COMPLIANCE

ADA guidelines state that fixtures mounted above 27" must not protrude more than 4" from the wall.

4"



Maximum: 48"
Recommended: 37"

SUGGESTED MOUNTING HEIGHTS from floor to bottom of dryer:

Men	45" (114 cm)
Women	43" (109 cm)
Teenagers	41" (104 cm)
Small Children	35" (89 cm)
Accessible	37" (94 cm)

¹Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.
²Special Paint powder-coated covers are available in many colors and textures. ³Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.



TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

**AUG
2020**

19TAS0638

XLERATOR® AND XLERATOR^{eco}® HAND DRYER

OPTIONS AND ACCESSORIES



XLERATOR and XLERATOR^{eco} are offered with several options and a complete line of accessories to customize the best hand drying solution for any restroom environment.

OPTIONS



HEPA FILTRATION SYSTEM

Excel Dryer offers a HEPA Filtration System proven to remove 99.99% of viruses from the airstream¹, and is the only one with a washable metal mesh pre-filter for reliable performance and extended filter life. The HEPA Filtration System is an optional feature or can be retrofitted into existing units.

PART#	Description
40525	XLERATOR/XLERATOR ^{eco} HEPA Filter RetroFit Kit
40520	XLERATOR/XLERATOR ^{eco} HEPA Filter Replacement
94	HEPA Pre-Filter Replacement Metal Mesh

NOTE: When ordering a new unit, add "H" to the model selected (e.g., XL-BW-H).
¹Based on testing performed by LMS Technologies, April 2020.



1.1" NOISE REDUCTION NOZZLE (1.1N)

Reduces the sound level by 9 decibels by significantly decreasing air deflection noise while only increasing dry time by approximately 3 seconds. Easily retrofitted into existing units or it can be purchased with new dryer models at no extra charge.

PART#	Description
62.2	1.1" Noise Reduction Nozzle

NOTE: When ordering a new unit, add "1.1N" to the model selected (e.g., XL-BW-1.1N).



WALL PLACARDS - GOING GREEN


These signs allow your customers to promote they have made the change from paper towels to High-Speed, Energy-Efficient Hand Dryers—helping them communicate the environmental benefits of the XLERATOR/XLERATOR^{eco} to their customers.

PART#	Description
676G	Wall Placard - Going Green (Green)
676W	Wall Placard - Going Green (White)

CUSTOM COVERS

Our cover finish options are the most diverse in the industry, including custom cover options for corporate branding or environmental messaging. Our exclusive Kolorfusion digital image technology is used to customize covers with graphics, team colors, corporate logos, green messaging or any other high-resolution imagery. Covers can also be painted with any RAL Color powder coat paint color or PVD coating such as Gold, Brass and Copper. Contact us for more information and pricing.





40502
(Dryer Sold Separately)

ADA-COMPLIANT RECESS KIT

Makes XLERATOR/XLERATOR^{eco} comply with the 4" ADA protrusion requirement of four inches. Also helps keep water off the walls and floor.

PART#	Description
40502	Recess Kit, Brushed Stainless Steel
40502SP	Recess Kit, Custom Color Painted

²Special paint colors include white, raven black, red baron and graphite. Custom paint colors are also available and require a minimum order of 5 or more. Call Excel Dryer for custom paint color options and pricing.



(Dryer Sold Separately)

- 40502W Recess Kit, White Paint
- 40502SP Recess Kit, Special Paint¹
- 40502GR Recess Kit, Graphite Textured Paint
- 40502R Recess Kit, Red Baron Paint



89W 89B 89S

MICROBAN®/ANTIMICROBIAL WALL GUARDS

Designed to fit securely below your Excel Hand Dryers, protecting your walls from water droplets that can be blown off wet hands by the powerful air stream. Microban technology inhibits the growth of bacteria and is built into the Wall Guard so it will not wash or wear away, lasting the lifetime of the product. Ideal for high-traffic restrooms, Wall Guards are hygienic and easy-to-clean.

PART#	Description
89W	Microban Wall Guard-White
89B	Microban Wall Guard-Black
89S	Wall Guard-Brushed Stainless Steel

³Sold as set: 1 box containing 2 wall guards



(Dryer Sold Separately)

Code Options
B Black Painted
W White Painted
GR Graphite Textured Paint
R Red Baron Paint
SP Custom Special Paint

XCHANGER® COMBO KIT

Allows you to completely retrofit your paper towel dispenser and waste receptacle with the XLERATOR/XLERATOR^{eco}. The XChanger is easily installed over the space left behind by the paper towel dispenser and will not cause damage to the existing wall surface. The XChanger Kit is also available in an ADA height compliant version, allowing full access for users in wheelchairs.

PART#	Description
40575	XChanger Combo Kit Comes with ADA Recess Kit 40502 and Standard XChanger 40550
40575SP	Custom Paint XChanger Combo Kit
40576	ADA XChanger Combo Kit for ADA Height Comes with ADA Recess Kit 40502 and 40551 ADA XChanger
40576SP	Custom Paint XChanger Combo Kit for ADA Height

⁴Special paint colors include white, raven black, red baron and graphite. Custom paint colors are also available and require a minimum order of 5 or more. Call Excel Dryer for custom paint color options and pricing.

